

G45SP SERIES CONTRACTOR'S GAUGE

DESCRIPTION

DESIGNED FOR PROFESSIONALS WHO DEMAND HIGH PERFORMANCE IN RUGGED ENVIRONMENTS, THIS GAUGE COMBINES PRECISION ENGINEERING WITH DURABLE CONSTRUCTION TO MEET THE NEEDS OF EVEN THE TOUGHEST JOBS. THE 4.5" CONTRACTOR'S PRESSURE GAUGE OFFERS THE DURABILITY, ACCURACY, AND DEPENDABILITY YOU NEED TO GET THE JOB DONE RIGHT.*ALWAYS INSTALL WITH A COIL SYPHON ON STEAM APPLICATIONS

SPECIFICATIONS

DIAL SIZE: 4.5"

CASE & RING: 304 SS W/ REMOVABLE RING

DIAL: WHITE-FINSIHED ALUMINUM WITH BLACK

Markings

LENS: ACRYLIC

POINTER: BLACK (FIELD ADJUSTABLE)

MOUNT: LOWER

WETTED PARTS: LEAD-FREE BRASS

MOVEMENT: BRASS

ACCURACY: ±1% GRADE A
CONNECTION SIZE: 1/4" NPT
ANSI STANDARD: B40.1

AMBIENT TEMP: -40 TO 158°F (-40 TO 70°C) **PROCESS TEMP:** -40 TO 158°F (-40 TO 70°C)

OPTIONS

- CERTIFICATE OF CALIBRATION
- CLEANED FOR OXYGEN SERVICE

PART NUMBER MATRIX

G45SPL 100 BLF-25

ORIENTATION

DIAL SIZE

CASE MATERIAL:
STAINLESS STEEL

LENS MATERIAL: PLASTIC

CONNECT. SIZE

WETTED PARTS

RANGE CODE

MOUNTING




RANGE TABLE

		PSI	
CODE	Range	Fig.	Div.
VAC	30"Hg - 0 vacuum	5	0.5
V15	30"Hg-0-15 psi	10/5	1/0.5
V30	30"Hg - 0 - 30 psi	10/5	1/0.5
V60	30"Hg - 0 - 60 psi	10/10	2/1
V100	30"Hg-0-100 psi	30/20	2/2
V150	30"Hg - 0 - 150 psi	30/20	5/2
V300	30"Hg - 0 - 300 psi	30/50	5/2
015	0 - 15 psi	3	0.2
030	0 - 30 PSI	5	0.5
060	0 - 60 PSI	10	1
100	0 - 100 PSI	10	1
160	0 - 160 PSI	20	2
200	0 - 200 PSI	20	2
300	0 - 300 PSI	50	5
400	0 - 400 PSI	50	5
600	0 - 600 PSI	50	10
1000	0 - 1000 PSI	100	20

*ALWAYS INSTALL WITH A COIL SYPHON ON STEAM APPLICATIONS
*GAUGE ACCESSORIES ON PAGE _

DIMENSIONS



313-241-0399

INFO@VOKERMFG.COM

